

Printing date 30.07.2018 Version number 1 Revision: 30.07.2018

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: PU BETON 4050 COMPONENT C

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

**Application of the substance / the mixture:** Priming

#### 1.3 Details of the supplier of the safety data sheet

### Manufacturer/Supplier:

PENETRON HELLAS S.A.

50, THRAKOMAKEDONON AV., 136 79 ACHARNES, GREECE

TEL.: +30 210 2448250 - FAX: + 30 210 2476803 Email: info@penetron.gr Site: www.penetron.gr

1.4 Emergency telephone number:



European Emergency Tel.: 112

### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture Classification according to Regulation EC No 1272/2008 CLP:



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

#### 2.2 Label elements

#### Labelling according to Regulation EC No 1272/2008 CLP:

The product is classified and labelled according to the CLP regulation.

#### **Hazard pictograms:**





GHS05 GHS07

Signal word: Danger

#### Hazard-determining components of labelling:

calcium dihydroxide

(Contd. on page 2)

Printing date 30.07.2018 Version number 1 Revision: 30.07.2018

Trade name: PU BETON 4050 COMPONENT C

(Contd. of page 1)

#### **Hazard statements:**

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

### **Precautionary statements**

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

#### **SECTION 3: Composition/information on ingredients**

# 3.2 Chemical characterisation: Mixtures

**Description:** Mixture: consisting of the following components.

Ingredients according Regulation (EU) 830/2015:		
CAS: 14808-60-7		50-100%
EINECS: 238-878-4	substance with a Community workplace exposure limit	
		25-50%
EINECS: 215-137-3	📀 Eye Dam. 1, H318; 🗘 Skin Irrit. 2, H315; STOT SE 3, H335	

### **SECTION 4: First aid measures**

# **4.1 Description of first aid measures**

General information: Seek immediate medical advice.

### After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

#### After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Avoid strong water jet-risk of cornea damage, consult a doctor.

#### After swallowing:

Drink plenty of water and provide fresh air. Call for a doctor immediately.

Seek immediate medical advice.

Never give anything by mouth to an unconscious person.

#### 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

# 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB

Printing date 30.07.2018 Version number 1 Revision: 30.07.2018

Trade name: PU BETON 4050 COMPONENT C

(Contd. of page 2)

#### **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

### Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray.

Use fire extinguishing methods suitable to surrounding conditions.

**5.2 Special hazards arising from the substance or mixture** No further relevant information available.

### 5.3 Advice for firefighters

# **Protective equipment:**

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

# **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Avoid the contact with eyes.

Avoid inhalation of dust.

Ensure adequate ventilation.

# **6.1.1 For non-emergency personnel** Avoid contact with dripping or leaking material

### **6.1.2** For emergency responders

First-aid responders must wear protectice clothing, gloves, goggles and respiratory device.

**6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

# 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Send for recovery or disposal in suitable receptacles.

#### **6.4 Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

No special measures required.

Open and handle receptacle with care.

Prevent formation of dust.

Avoid contact with skin, eyes and clothing.

Information about fire - and explosion protection: No special measures required.

### 7.2 Conditions for safe storage, including any incompatibilities

**Storage:** Store in cool, dry conditions in well sealed receptacles.

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Not required.

#### Further information about storage conditions:

Keep container tightly sealed.

Store under lock and key and with access restricted to technical experts or their assistants only.

(Contd. on page 4)

Printing date 30.07.2018 Version number 1 Revision: 30.07.2018

Trade name: PU BETON 4050 COMPONENT C

(Contd. of page 3)

**7.3 Specific end use(s)** No further relevant information available.

# **SECTION 8: Exposure controls/personal protection**

### **8.1 Control parameters**

# Ingredients with limit values that require monitoring at the workplace:

CAS: 14808-60-7 Quartz (SiO2)

BOELV (EU) Long-term value: 0.1\* mg/m<sup>3</sup>

\*respirable fraction

CAS: 1305-62-0 calcium dihydroxide

WEL (Great Britain) Long-term value: 5 mg/m³
IOELV (EU) Short-term value: 4 mg/m³
Long-term value: 1 mg/m³
Respirable fraction

#### **8.2** Exposure controls

# 8.2.1. Appropriate engineering controls

Take appropriate protective measures with regard to the handling of chemicals and mixtures.

### Personal protective equipment

#### **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

### **Respiratory protection:**



Use suitable respiratory protective device in case of insufficient ventilation.

#### **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation **Material of gloves** 

# Butyl rubber, BR - 0,7 mm

Nitrile rubber, NBR- 0,4 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 30.07.2018 Version number 1 Revision: 30.07.2018

Trade name: PU BETON 4050 COMPONENT C

(Contd. of page 4)

# Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended. **Eye protection:** 



Tightly sealed goggles

#### **Body protection:**



Protective work clothing

#### **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties

**General Information** 

**Appearance:** 

Form: Solid Colour: Solid Grey

Odour: Uncharacteristic.
Odour threshold: Not determined

**pH value:** Not applicable **Initial boiling point and boiling range:** 2,230 °C

Flash point: Not Flammable

Flammability (solid, gas): Not determined

**Auto-ignition temperature:** Not determined

**Decomposition temperature:** Not determined

**Auto-ignition temperature:** Product is not selfigniting.

**Explosive properties:** Product does not present an explosion hazard.

**Explosion limits:** 

Lower: Not determined Upper: Not determined

**Vapour pressure:** Not applicable

Density at 20 °C:2.45 g/cm³Relative densityNot determinedVapour densityNot applicableEvaporation rateNot applicable

(Contd. on page 6)

Printing date 30.07.2018 Version number 1 Revision: 30.07.2018

Trade name: PU BETON 4050 COMPONENT C

(Contd. of page 5)

Solubility in / Miscibility with

water: Insoluble

Partition coefficient: n-octanol/water: Not determined

Viscosity:

**Dynamic:** Not applicable **Kinematic:** Not applicable

**Solvent content:** 

Solids content: 100.0 %

**9.2 Other information** No further relevant information available.

#### **SECTION 10: Stability and reactivity**

10.1 Reactivity Stable under normal conditions

10.2 Chemical stability Material is stable under normal conditions.

Thermal decomposition / conditions to be avoided Stable at environment temperature.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid No further relevant information available.

**10.5 Incompatible materials** No further relevant information available.

10.6 Hazardous decomposition products No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

#### LD/LC50 values relevant for classification:

#### CAS: 1305-62-0 calcium dihydroxide

Oral LD50 >2,000 mg/kg (rat) (OECD 425)
Dermal LD50 >2,500 mg/kg (rabbit) (OECD 402)

#### Skin corrosion/irritation

Causes skin irritation.

### Serious eye damage/irritation

Causes serious eye damage.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Repeated dose toxicity** Based on the data, the classification criteria are not fulfilled.

# CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

#### STOT-single exposure

The product is classified as Specific Target Organ Toxicity after single exposure Category 3 May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

GB

Printing date 30.07.2018 Version number 1 Revision: 30.07.2018

Trade name: PU BETON 4050 COMPONENT C

(Contd. of page 6)

#### **SECTION 12: Ecological information**

12.1 Toxicity

Aquatic toxicity: No further relevant information available.

12.2 Persistence and degradability No further relevant information available.

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

Additional ecological information:

General notes: Must not reach sewage water or drainage ditch undiluted or unneutralised.

12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

**12.6 Other adverse effects** No further relevant information available.

### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

#### Recommendation



Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

Waste disposal key: 10 13 04 wastes from calcination and hydration of lime

**Uncleaned packaging:** 

**Recommendation:** Disposal must be made according to official regulations.

#### **SECTION 14: Transport information**

14.1 UN-Number

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards: Not applicable.14.6 Special precautions for user Not applicable.

14.7 Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

UN "Model Regulation": Void

GB

Printing date 30.07.2018 Version number 1 Revision: 30.07.2018

Trade name: PU BETON 4050 COMPONENT C

(Contd. of page 7)

#### **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH Regulation 1907/2006/EC Regulation (EU) 2015/830

CLP Regulation 1272/2008/EC

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Council Directive 94/33/EC on the protection of young people at work, as ammended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as ammended

#### Directive 2012/18/EU

Named dangerous substances - ANNEX I Substance is not listed.

## **National regulations:**

# Other regulations, limitations and prohibitive regulations

# Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

# **Relevant phrases**

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

### **Training hints**

Suitable training on safety in handling, storing and converting the product should be given to the employees based on all the existing information.

### **Department issuing SDS:**



**SUSTCHEM Engineering SA** 

**REACH & Chemical Services Department** 

144, 3rd Septemvriou, GR 112 51, Athens, Greece

Tel.: +30 210 8252510 Fax: +30 210 8252575

E-mail: info@suschem.gr Website: www.sustchem.gr

### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 9)

(Contd. of page 8)

# Safety data sheet complying with Regulation 1907/2006/EC (REACH Regulation), EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 30.07.2018 Version number 1 Revision: 30.07.2018

Trade name: PU BETON 4050 COMPONENT C

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3