

**Safety data sheet**  
**complying with Regulation 1907/2006/EC (REACH Regulation),**  
**EU 2020/878 and Regulation No 1272/2008/EC (CLP)**

Printing date 16.02.2022

Version number 8 (replaces version 7)

Revision: 16.02.2022

**\* SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier****Trade name:** S-Bond FLEX**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

**Application of the substance / the mixture:** Adhesive for wood flooring bonding.**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

PENETRON HELLAS S.A.

50, THRAKOMAKEDONON AV., 136 79 ACHARNES, GREECE

TEL.: +30 210 2448250 - FAX: + 30 210 2476803

Email: info@penetron.gr Site: www.penetron.gr

**1.4 Emergency telephone number:**

European Emergency Tel.: 112

**\* SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Classification according to Regulation EC No 1272/2008 CLP:**

This product does not meet the criteria for classification in any hazard class according to Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures.

**2.2 Label elements****Labelling according to Regulation EC No 1272/2008 CLP:** Void**Hazard pictograms:** Void**Signal word:** Void**Hazard statements:** Void**Additional information:**

EUH208 Contains N-(3-(trimethoxysilyl)propyl)ethylenediamine, trimethoxyvinylsilane. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

**2.3 Other hazards****Results of PBT and vPvB assessment**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**PBT:** Not applicable.**vPvB:** Not applicable.**\* SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture: consisting of the following components.

(Contd. on page 2)

GB

**Safety data sheet**  
**complying with Regulation 1907/2006/EC (REACH Regulation),**  
**EU 2020/878 and Regulation No 1272/2008/EC (CLP)**

Printing date 16.02.2022

Version number 8 (replaces version 7)

Revision: 16.02.2022

**Trade name:** S-Bond FLEX

(Contd. of page 1)

**Ingredients according Regulation (EU) 2020/878:**

CAS: 1760-24-3 EINECS: 217-164-6 Reg.nr.: 01-2119970215-39-XXXX	N-(3-(trimethoxysilyl)propyl)ethylenediamine ⚠ STOT RE 2, H373; ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317	≥0.89-<1%
CAS: 2768-02-7 EINECS: 220-449-8 Index number: 014-049-00-0 Reg.nr.: 01-2119513215-52-XXXX	trimethoxyvinylsilane ⚠ Flam. Liq. 3, H226; ⚠ Acute Tox. 4, H332; Skin Sens. 1B, H317	≥0.89-<1%
CAS: 67-56-1 EINECS: 200-659-6 Index number: 603-001-00-X	methanol ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT SE 1, H370 Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %	≥0-<0.05%

**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Take affected persons out into the fresh air.

In all cases call a doctor

**After inhalation:**

Keep patient calm, remove to fresh air.

Call a doctor immediately.

**After skin contact:**

Remove contaminated clothing.

Wash the skin immediately with soap and water.

If skin irritation continues, consult a doctor.

**After eye contact:**

Remove immediately with a clean cloth or paper and wash affected area with soap and water.

**After swallowing:**

Rinse mouth with water.

Seek immediate medical advice.

**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

Consult a doctor if symptoms are severe or in the case of persistent irritation of the skin.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:** Carbon dioxide, foam, powder and water spray.**For safety reasons unsuitable extinguishing agents:** None in particular.**5.2 Special hazards arising from the substance or mixture** No further relevant information available.**5.3 Advice for firefighters****Protective equipment:**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

(Contd. on page 3)

**Safety data sheet**  
**complying with Regulation 1907/2006/EC (REACH Regulation),**  
**EU 2020/878 and Regulation No 1272/2008/EC (CLP)**

Printing date 16.02.2022

Version number 8 (replaces version 7)

Revision: 16.02.2022

**Trade name:** S-Bond FLEX

(Contd. of page 2)

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures:**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.1.2 For emergency responders**

First-aid responders must wear protective clothing, gloves, goggles and respiratory device with filter type A.

**6.2 Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.

**6.3 Methods and material for containment and cleaning up:**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10.

Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired.

**6.4 Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage****7.1 Precautions for safe handling**

Before handling the product, consult all the other sections of this material safety data sheet.

Avoid leakage of the product into the environment.

Do not eat, drink or smoke during use.

Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

**Information about fire - and explosion protection:**

Keep it in a dry, cool, well ventilated, fixed in advance place, away from sources of heat, flames, ignition and direct sunlight.

**7.2 Conditions for safe storage, including any incompatibilities****Storage:****Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Store under cover out of direct sunlight.

Keep only in the original container.

**Further information about storage conditions:** None.

**Storage class:** TRGS 510 (Germany): 10

**7.3 Specific end use(s)** No further relevant information available.

GB

(Contd. on page 4)

**Safety data sheet**  
**complying with Regulation 1907/2006/EC (REACH Regulation),**  
**EU 2020/878 and Regulation No 1272/2008/EC (CLP)**

Printing date 16.02.2022

Version number 8 (replaces version 7)

Revision: 16.02.2022

**Trade name:** S-Bond FLEX

(Contd. of page 3)

\* **SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 67-56-1 methanol**

WEL (Great Britain)	Short-term value: 333 mg/m <sup>3</sup> , 250 ppm Long-term value: 266 mg/m <sup>3</sup> , 200 ppm Sk
IOELV (EU)	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm Skin

**DNELs**

N-(3-(trimethoxysilyl)propyl)ethylenediamine | CasNo: 1760-24-3.

Consumers:

Inhalation: chronic systemic effect - 8.7 mg/m<sup>3</sup>.Dermal: Acute systemic effect - 17 mg/kg bw/d.  
chronic systemic effect - 2.5 mg/kg bw/d.

Workers:

Inhalation: chronic systemic effect - 35.3 mg/m<sup>3</sup>.

Dermal: Acute &amp; chronic systemic effect - 5 mg/kg bw/d.

Trimethoxyvinylsilane | CasNo: 2768-02-7.

Consumers:

Oral: chronic systemic effect - 0.3 mg/kg/d

Inhalation: Acute systemic effect - 93.4 mg/m<sup>3</sup>  
chronic systemic effect - 1.04 mg/m<sup>3</sup>Dermal: Acute systemic effect - 26.9 mg/kg/d  
chronic systemic effect - 0.3 mg/kg/d

Workers:

Inhalation: chronic systemic effect - 4.9 mg/m<sup>3</sup>

Dermal: chronic systemic effect - 0.69 mg/kg/d

**PNECs**

N-(3-(trimethoxysilyl)propyl)ethylenediamine | CasNo: 1760-24-3.

fresh water 0.062 mg/l

marine water 0,0062 mg/l

sediment in fresh water 0.22 mg/kg

sediment in marine water 0,022 mg/kg

for water, intermittent release of 0.62 mg/l

for STP microorganisms 25 mg/l

for the terrestrial compartment 0,0085 mg/kg

Trimethoxyvinylsilane | CasNo: 2768-02-7.

fresh water 0.34 mg/l

marine water 0,034 mg/l

sediment in fresh water 0.27 mg/kg

for water, intermittent release of 3.4 mg/l

for STP micro-organisms 110 mg/l

for the terrestrial compartment of 0.046 mg/kg

(Contd. on page 5)

GB

**Safety data sheet**  
**complying with Regulation 1907/2006/EC (REACH Regulation),**  
**EU 2020/878 and Regulation No 1272/2008/EC (CLP)**

Printing date 16.02.2022

Version number 8 (replaces version 7)

Revision: 16.02.2022

**Trade name:** S-Bond FLEX

(Contd. of page 4)

**8.2 Exposure controls****8.2.1. Appropriate engineering controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

Avoid contact with skin and eyes.

Do not eat, drink or smoke while using the product.

Do not breathe vapours or mists.

Wash the hands thoroughly after handling

**Respiratory protection:**

In case of exceeding the threshold value (eg, TLV-TWA) of the substance or one or more of the substances present in the product, it is advisable to wear a mask with filter type A for organic vapors, the class (1, 2 or 3) must be chosen according to the limit concentration of use (1000, 5000 or 10000 ppm) (ref. standard EN 14387).

**Hand protection**

Protective gloves resistant to chemicals (standard EN 374-1)

**Material of gloves**

NBR (Nitrile rubber)

thickness 0.4 mm, penetration time > 480 minutes

Contaminated gloves should be removed.

**Penetration time of glove material**

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

**Eye/face protection**

Safety glasses with side-shields (frame goggles) (e.g. EN 166)

**Body protection:**

Wear category I professional long-sleeved overalls and safety footwear (ref. Directive 89/686/CEE and standard EN ISO 20344). Wash body with soap and water after removing overalls.

**Environmental exposure controls**

Emissions of production processes, including ventilators, should be controlled to comply with environmental regulations.

Product residues should not be disposed of without control in the discharge waters or aquifers.

GB

(Contd. on page 6)

**Safety data sheet**  
**complying with Regulation 1907/2006/EC (REACH Regulation),**  
**EU 2020/878 and Regulation No 1272/2008/EC (CLP)**

Printing date 16.02.2022

Version number 8 (replaces version 7)

Revision: 16.02.2022

Trade name: S-Bond FLEX

(Contd. of page 5)

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**General Information**

<b>Physical state</b>	Paste
<b>Colour:</b>	Brown
<b>Odour:</b>	typical
<b>Odour threshold:</b>	Not determined
<b>Melting point/freezing point:</b>	Not determined
<b>Boiling point or initial boiling point and boiling range</b>	Not determined
<b>Flammability</b>	Not applicable
<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	Not determined
<b>Upper:</b>	Not determined
<b>Flash point:</b>	Not Flammable
<b>Decomposition temperature:</b>	Not determined
<b>pH</b>	Not determined
<b>Viscosity:</b>	
<b>Kinematic viscosity</b>	Not determined
<b>Dynamic:</b>	17000-27000 cps (UNI EN ISO 3219)
<b>Solubility</b>	
<b>water:</b>	Insoluble
<b>Partition coefficient n-octanol/water (log value)</b>	Not determined
<b>Vapour pressure:</b>	Not determined
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	1.7-1.74 g/cm <sup>3</sup> (ISO 1183-1 A)
<b>Relative density</b>	Not determined
<b>Vapour density</b>	Not determined

**9.2 Other information**

<b>Appearance:</b>	
<b>Form:</b>	Paste
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Auto-ignition temperature:</b>	Not determined
<b>Explosive properties:</b>	Product does not present an explosion hazard.
<b>Solvent content:</b>	
<b>VOC (EC)</b>	VOC (Directive 2010/75/EC): 0
<b>Cloud point / clarification point:</b>	
<b>Oxidising properties</b>	No data available
<b>Evaporation rate</b>	Not determined

**Information with regard to physical hazard classes**

<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	Void
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Void
<b>Flammable solids</b>	Void

(Contd. on page 7)

**Safety data sheet**  
**complying with Regulation 1907/2006/EC (REACH Regulation),**  
**EU 2020/878 and Regulation No 1272/2008/EC (CLP)**

Printing date 16.02.2022

Version number 8 (replaces version 7)

Revision: 16.02.2022

**Trade name:** S-Bond FLEX

(Contd. of page 6)

<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

**SECTION 10: Stability and reactivity****10.1 Reactivity**

Product reacts slowly with water (ambient humidity) turning into a rubbery solid and producing methanol.

**10.2 Chemical stability****Thermal decomposition / conditions to be avoided**

No decomposition if used and stored according to specifications.

Stable at environment temperature.

**10.3 Possibility of hazardous reactions** No dangerous reactions known.**10.4 Conditions to avoid** Moisture**10.5 Incompatible materials** Water**10.6 Hazardous decomposition products**

Nitrogen oxides

Carbon monoxide and carbon dioxide

**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:****CAS: 1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine**

Oral	LD50	2,295 mg/kg (rat)
------	------	-------------------

Dermal	LD50	>2,000 mg/kg
--------	------	--------------

Inhalative	LC50/4h (dusts and mists)	1.49 mg/l (rat)
------------	---------------------------	-----------------

**CAS: 2768-02-7 trimethoxyvinylsilane**

Oral	LD50	7,178 mg/kg (rat)
------	------	-------------------

Dermal	LD50	3,200 mg/kg (rabbit)
--------	------	----------------------

Inhalative	LC50/4 h (vapour)	16.8 mg/l (rat)
------------	-------------------	-----------------

**CAS: 67-56-1 methanol**

Oral	LD50	5,000 mg/kg (rat)
------	------	-------------------

		15,800 mg/kg (rabbit)
--	--	-----------------------

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

(Contd. on page 8)

**Safety data sheet**  
**complying with Regulation 1907/2006/EC (REACH Regulation),**  
**EU 2020/878 and Regulation No 1272/2008/EC (CLP)**

Printing date 16.02.2022

Version number 8 (replaces version 7)

Revision: 16.02.2022

**Trade name:** S-Bond FLEX

(Contd. of page 7)

**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**Additional toxicological information:****Repeated dose toxicity** Based on available data, the classification criteria are not met.**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:****CAS: 1760-24-3 N-(3-(trimethoxysilyl)propyl)ethylenediamine**

EC50 (72h) 126 mg/l (ssu)

EC50 (48h) 81 mg/l (Daphnia magna)

LC50 (96h) 344 mg/l (Brachydanio rerio)

**CAS: 2768-02-7 trimethoxyvinylsilane**

NOEC 25 mg/l (Selenastrum capricornutum)

LC50 (96h) 191 mg/l (fis)

**CAS: 67-56-1 methanol**

EC50 (48h) &gt;10,000 mg/l (daphnia magna)

LC50 (96h) 15,400-29,400 mg/l (fis)

**12.2 Persistence and degradability**

CAS: 1760-24-3 | N-(3-(trimethoxysilyl)propyl)ethylenediamine

Not rapidly degradable

CAS: 2768-02-7 | Trimethoxyvinylsilane

Not rapidly degradable.

CAS: 67-56-1 Methanol

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

**12.3 Bioaccumulative potential**

CAS: 67-56-1 | Methanol

Partition coefficient: n-octanol/water: -0,77

BCF: 0,2

**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment**

Based on available data, the product does not contain PBT or vPvB in an amount greater than 0.1%.

**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.**12.7 Other adverse effects** No further relevant information available.

GB

(Contd. on page 9)

**Safety data sheet**  
**complying with Regulation 1907/2006/EC (REACH Regulation),**  
**EU 2020/878 and Regulation No 1272/2008/EC (CLP)**

Printing date 16.02.2022

Version number 8 (replaces version 7)

Revision: 16.02.2022

**Trade name:** S-Bond FLEX

(Contd. of page 8)

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation**

Dispose according to National Regulations.

Reuse, when possible. Product residues should be considered special hazardous waste.

The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**Uncleaned packaging:****Recommendation:**

Disposal must be made according to official regulations.

Packaging may be reused or recycled after cleaning.

**SECTION 14: Transport information****14.1 UN number or ID number**

ADR, ADN, IMDG, IATA Void

**14.2 UN proper shipping name**

ADR, ADN, IMDG, IATA Void

**14.3 Transport hazard class(es)**

ADR, ADN, IMDG, IATA

Class Void

**14.4 Packing group**

ADR, IMDG, IATA Void

**14.5 Environmental hazards:** Not applicable.**14.6 Special precautions for user** Not applicable.**14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

UN "Model Regulation": Void

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH Regulation 1907/2006/EC

Regulation (EU) 2020/878

CLP Regulation 1272/2008/EC

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Council Directive 94/33/EC on the protection of young people at work, as amended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

(Contd. on page 10)

GB

**Safety data sheet**  
**complying with Regulation 1907/2006/EC (REACH Regulation),**  
**EU 2020/878 and Regulation No 1272/2008/EC (CLP)**

Printing date 16.02.2022

Version number 8 (replaces version 7)

Revision: 16.02.2022

**Trade name:** S-Bond FLEX

(Contd. of page 9)

**National regulations:****Other regulations, limitations and prohibitive regulations****Substances of very high concern (SVHC) according to REACH, Article 57**

It doesn't contain substances of very high concern (SVHC).

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H311 Toxic in contact with skin.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.


H331 Toxic if inhaled.

H332 Harmful if inhaled.

H370 Causes damage to organs.

H373 May cause damage to organs through prolonged or repeated exposure.

**Department issuing SDS:**

**SUST**  SUSTCHEM S.A.  
**CHEM**  
CONSULTING REACH & Chemical Services Department  
 A: 144, 3rd Septemvriou, GR 112 51 | Athens, Greece  
 T: +30 210 8252510 | F: +30 210 8252575  
 W: www.sustchem.gr | E: info@suschem.gr

**Version number of previous version: 7****Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

(Contd. on page 11)

**Safety data sheet**  
**complying with Regulation 1907/2006/EC (REACH Regulation),**  
**EU 2020/878 and Regulation No 1272/2008/EC (CLP)**

Printing date 16.02.2022

Version number 8 (replaces version 7)

Revision: 16.02.2022

**Trade name:** S-Bond FLEX

(Contd. of page 10)

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

**\* Data compared to the previous version altered.**

GB