

SOLVENT MIXTURE ESPECIALLY SUITABLE FOR POLYURETHANE RESIN SEALERS
ALIGNED TO THINNING AND CLEANING**DESCRIPTION**

Solvent mixture aligned with polyurethane resin sealers. Use as thinner of polyurethane sealers, which contain solvents (PU 880, PU 881, PU 881 EL+, PU 882 and so on), as well as for epoxy resin sealers (EP 860, EP 861 and others) within the manufacturer's recommendation. Use to clean tools, as long as the resin hasn't been cured yet.

TECHNICAL CHARACTERISTICS

Density | 0.9 g/cm³

The aforementioned results are related to average laboratory test results. In reality, the climate changes, such as temperature, moisture and surface porosity, may change these results.

SPECIAL CONSIDERATIONS

Flammable. Note the safety data sheet information. To clean tools, remove the necessary amount in a separate, reclosable container. Use a paint brush for cleaning. Dilute epoxy resin only according to the manufacturer's recommendation.

Contact PENETRON HELLAS S.A. for further information, regarding your project.

PACKAGING

VR 28 is available 10 Lt container.

STORAGE / SHELF LIFE

Always seal tight after usage. Store in a suitable place.

SAFE HANDLING INFORMATION

Avoid skin and eye contact. If contact is made, flush areas with plenty of water and seek medical advice. Protective gloves, mask and goggles should be worn. For further information, please refer to Safety Data Sheet. PENETRON HELLAS S.A. has recently updated Safety Data Sheet on the safe use of PENETRON® products. Each Safety Data Sheet contains health and safety information for the protection of your employees and your customers. KEEP OUT OF REACH OF CHILDREN.

WARRANTY – DISCLAIMER

PENETRON HELLAS S.A. warrants that its products are manufactured under certified ISO Standard procedures, are of excellent quality and shall be free from material defects and contain all components in their proper proportion. Should any of the products be proven defective, the liability to PENETRON HELLAS S.A. shall be limited to replacement of the material proven to be defective, since the standard application procedures have been met and the suitability of the product for the particular application has been proven. PENETRON HELLAS S.A. makes no warranty as to merchantability of fitness for a particular purpose. User, after contacting the distributor of the product, shall determine the suitability of the product for his intended use and assume all risks and liability in connection therewith. While every care has been taken, the information provided in this product's data sheet make no part of any contract. All recommendations, technical data and test data contained in this product's data sheet are based upon the results of control laboratory tests or in actual field tests. However, PENETRON HELLAS S.A. makes no warranty of any kind, concerning these data. In any case, these data are given in good faith based in the PENETRON HELLAS S.A. experience, till the publication of this sheet. Due to variance in storage, handling and applications of the materials, PENETRON HELLAS S.A. accepts no liability for the results obtained. It is suggested that potential users try small applications to determine the suitability of each individual product for their specific requirements. The users should always refer to the most recent edition of the product's data sheet. PENETRON HELLAS S.A. may particularly differentiate its versions of the product's data sheet compared with those of PENETRON INTERNATIONAL LTD or respective PENETRON companies worldwide. These changes are due to text formatting, different application weathering and procedures or different product names and aim at the optimal consumer information

PENETRON HELLAS S.A.
G.E.MH. No: 07278001000
Athens Headquarters - Greece
50 - 52, Thrakomakedonon Av.
136 79 Acharnes, Greece
T: +30 210 2448250
F: +30 210 2476803
info@penetron.gr, www.penetron.gr