

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 26.07.2018

Version number 1

Revision: 26.07.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** EP 860 Component A**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Application of the substance / the mixture:

Epoxy Coating

Epoxy resin

Sealant

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

PENETRON HELLAS S.A. G.E.MH. No: 07278001000

50, THRAKOMAKEDONON AV., 136 79 ACHARNES, GREECE

TEL.: +30 210 2448250 - FAX: + 30 210 2476803

Email: info@penetron.gr Site: www.penetron.gr

1.4 Emergency telephone number:

European Emergency Tel.: 112

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation EC No 1272/2008 CLP:**

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

2.2 Label elements**Labelling according to Regulation EC No 1272/2008 CLP:**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 26.07.2018

Version number 1

Revision: 26.07.2018

Trade name: EP 860 Component A

(Contd. of page 1)

Hazard pictograms:

GHS02 GHS07 GHS08

Signal word: Danger**Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)
 Xylene

Hazard statements:

H225 Highly flammable liquid and vapour.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.
 H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3 Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.
vPvB: Not applicable.

SECTION 3: Composition/information on ingredients**3.2 Chemical characterisation: Mixtures****Description:** Mixture: consisting of the following components.**Ingredients according Regulation (EU) 830/2015:**

CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26-XXXX	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700) ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-XXXX	Xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%

(Contd. on page 3)

GB

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 26.07.2018

Version number 1

Revision: 26.07.2018

Trade name: EP 860 Component A

(Contd. of page 2)

CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3	1-methoxy-2-propanol ☠ Flam. Liq. 3, H226; ☠ STOT SE 3, H336	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-XXXX	2-methoxy-1-methylethyl acetate ☠ Flam. Liq. 3, H226	2.5-10%

Additional information: For the wording of the hazard statements, see section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Take affected persons out into the fresh air.
 Seek immediate medical advice.

After inhalation:

Remove the victim into fresh air.

In case of unconsciousness place patient stably in side position for transportation.

Seek medical treatment in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

In case of skin irritation, consult a physician.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Remove contact lenses and continue rinsing for several minutes

Avoid strong water jet-risk of cornea damage, consult a doctor.

After swallowing: Consult a physician or poison control center.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fire with foam.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters**Protective equipment:**

During fire-fighting wear suitable respiratory device (SCBA) with a full face-piece operated in positive pressure mode.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures:**

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 26.07.2018

Version number 1

Revision: 26.07.2018

Trade name: EP 860 Component A

(Contd. of page 3)

6.1.2 For emergency responders

First-aid responders must wear protective clothing, gloves, goggles and respiratory device.

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material: (sand, diatomite, acid binders, universal binders and sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Ensure good ventilation.

Do not breathe vapor or mist.

Take protective measures against electrostatic discharge.

Avoid contact with eyes, hands and clothing.

Information about fire - and explosion protection: No special measures required.**7.2 Conditions for safe storage, including any incompatibilities****Storage:** Store in cool, dry conditions in well sealed receptacles.**Requirements to be met by storerooms and receptacles:** Prevent any seepage into the ground.**Information about storage in one common storage facility:**

Store away from oxidizing agents.

Store away from foodstuffs and feed products

Store away from amines.

Further information about storage conditions:

Keep container tightly sealed.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 1330-20-7 Xylene**

WEL (Great Britain)	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
---------------------	--

IOELV (EU)	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
------------	--

CAS: 107-98-2 1-methoxy-2-propanol

WEL (Great Britain)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
---------------------	---

(Contd. on page 5)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 26.07.2018

Version number 1

Revision: 26.07.2018

Trade name: EP 860 Component A

(Contd. of page 4)

IOELV (EU)	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Skin
CAS: 108-65-6 2-methoxy-1-methylethyl acetate	
WEL (Great Britain)	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
IOELV (EU)	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin

Ingredients with biological limit values:**CAS: 1330-20-7 Xylene**

BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
----------------------	--

8.2 Exposure controls**8.2.1. Appropriate engineering controls**

Take appropriate protective measures with regard to the handling of chemicals and mixtures.

Personal protective equipment**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Be sure to clean skin thoroughly after work and before breaks.

Remove contaminated clothing and protective equipment before entering eating areas.

Do not eat, drink or smoke while using the product.

Do not inhale dust / smoke / mist.

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR - 0,7 mm

Nitrile rubber, NBR- 0,4 mm

Neoprene

(Contd. on page 6)

GB

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 26.07.2018

Version number 1

Revision: 26.07.2018

Trade name: EP 860 Component A

(Contd. of page 5)

Viton

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye protection:

Tightly sealed goggles

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****General Information****Appearance:**

Form:	Liquid
Colour:	Light brown
Odour:	Solvent
Odour threshold:	Not determined

pH value: Not determined

Initial boiling point and boiling range: 120 °C

Flash point: 21 °C

Flammability (solid, gas): Not applicable

Auto-ignition temperature: 270 °C

Decomposition temperature: Not determined

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

Explosion limits:

Lower:	1.5 Vol %
Upper:	13.7 Vol %

Vapour pressure at 20 °C: 12 hPa

Density at 20 °C: 1.02 g/cm³ (DIN EN ISO 2811-2)

Relative density Not determined

(Contd. on page 7)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 26.07.2018

Version number 1

Revision: 26.07.2018

Trade name: EP 860 Component A

(Contd. of page 6)

Vapour density Not determined
Evaporation rate Not determined

Solubility in / Miscibility with water: Not miscible

Partition coefficient: n-octanol/water: Not determined

Viscosity:

Dynamic at 20 °C: 280 mPas (DIN EN ISO 3219)

Kinematic: Not determined

Solvent content:

VOC (EC) 55.03 %

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity Stable under normal conditions

10.2 Chemical stability Material is stable under normal conditions.

Thermal decomposition / conditions to be avoided Stable at environment temperature.

10.3 Possibility of hazardous reactions

Reacts with acids, alkalis and oxidising agents.

Reacts with amines.

Reacts with alcohols.

Exothermic reaction.

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials No further relevant information available.

10.6 Hazardous decomposition products Irritant gases/vapours

SECTION 11: Toxicological information**11.1 Information on toxicological effects**

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**ATE (Acute Toxicity Estimates)**

Dermal	LD50	2,200-4,400 mg/kg
Inhalative	LC50/4 h (vapour)	22-44 mg/l

CAS: 107-98-2 1-methoxy-2-propanol

Oral	LD50	4,016 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8,532 mg/kg (rat)
------	------	-------------------

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

(Contd. on page 8)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 26.07.2018

Version number 1

Revision: 26.07.2018

Trade name: EP 860 Component A

(Contd. of page 7)

Respiratory or skin sensitisation

May cause an allergic skin reaction.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure**

The product is classified as Specific Target Organ Toxicity after single exposure Category 3

May cause respiratory irritation. May cause drowsiness or dizziness.

STOT-repeated exposure

STOT Repeated Exposure Category 2

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Based on available data, the classification criteria are not met.**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:****CAS: 108-65-6 2-methoxy-1-methylethyl acetate**

EC50-48h >500 mg/l (daphnia magna)

LC50-96h 100-180 mg/l (Con)


CAS: 107-98-2 1-methoxy-2-propanol

EC50-48h 23.300 mg/l (daphnia magna)

LC50-96h 6.812 mg/l (Leuciscus Idus)

12.2 Persistence and degradability No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation**

Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

Waste disposal key:

08 04 09 - waste adhesives and sealants containing organic solvents or other dangerous substances.

(Contd. on page 9)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 26.07.2018

Version number 1

Revision: 26.07.2018

Trade name: EP 860 Component A

(Contd. of page 8)

Uncleaned packaging:**Recommendation:**

Disposal must be made according to official regulations.

Packaging may be reused or recycled after cleaning.

SECTION 14: Transport information**14.1 UN-Number****ADR, IMDG, IATA**

UN1866

14.2 UN proper shipping name**ADR**

1866 RESIN SOLUTION

IMDG, IATA

RESIN SOLUTION

14.3 Transport hazard class(es)**ADR, IMDG, IATA****Class**

3 Flammable liquids.

Label

3

14.4 Packing group**ADR, IMDG, IATA**

III

14.5 Environmental hazards:Product contains environmentally hazardous substances:
reaction product: bisphenol-A-(epichlorhydrin) epoxy resin
(number average molecular weight ≤ 700)**14.6 Special precautions for user**

Warning: Flammable liquids.

Danger code (Kemler):

-

EMS Number:F-E,S-E**Stowage Category**

B

Stowage Code

SW2 Clear of living quarters.

14.7 Transport in bulk according to Annex II of**Marpol and the IBC Code**

Not applicable.

Transport/Additional information:**ADR****Limited quantities (LQ)**

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

Transport category

3

Tunnel restriction code

E

IMDG**Limited quantities (LQ)**

5L

Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

GB

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 26.07.2018

Version number 1

Revision: 26.07.2018

Trade name: EP 860 Component A

UN "Model Regulation":

UN 1866 RESIN SOLUTION, 3, III

(Contd. of page 9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH Regulation 1907/2006/EC

Regulation (EU) 2015/830

CLP Regulation 1272/2008/EC

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Council Directive 94/33/EC on the protection of young people at work, as amended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as amended

Directive 2012/18/EU

Named dangerous substances - ANNEX I

None of the ingredients is listed.

Substance is not listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

Training hints

Suitable training on safety in handling, storing and converting the product should be given to the employees based on all the existing information.

(Contd. on page 11)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 26.07.2018

Version number 1

Revision: 26.07.2018

Trade name: EP 860 Component A

(Contd. of page 10)

Department issuing SDS:

SUSTCHEM Engineering SA
 REACH & Chemical Services Department
 144, 3rd Septemvriou, GR 112 51, Athens, Greece
 Tel.: +30 210 8252510 Fax: +30 210 8252575
 E-mail: info@suschem.gr
 Website: www.sustchem.gr

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Flam. Liq. 2: Flammable liquids – Category 2
 Flam. Liq. 3: Flammable liquids – Category 3
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1

GB