

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 30.07.2018

Version number 1

Revision: 30.07.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** PU BETON 4006 COMPONENT B**CAS Number:**

9016-87-9

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture:

Coating

Hardening agent/ Curing agent

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

PENETRON HELLAS S.A.

50, THRAKOMAKEDONON AV., 136 79 ACHARNES, GREECE

TEL.: +30 210 2448250 - FAX: + 30 210 2476803

Email: info@penetron.gr Site: www.penetron.gr

1.4 Emergency telephone number:

European Emergency Tel.: 112

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation EC No 1272/2008 CLP:**

GHS08 health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements**Labelling according to Regulation EC No 1272/2008 CLP:**

The substance is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 30.07.2018

Version number 1

Revision: 30.07.2018

Trade name: PU BETON 4006 COMPONENT B

(Contd. of page 1)

Hazard pictograms:

GHS07 GHS08

Signal word: Danger**Hazard-determining components of labelling:**

diphenylmethanediisocyanate, isomeres and homologues

Hazard statements:

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.1 Chemical characterisation: Substances****CAS No. Description**

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues 100% w/w

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Change contaminated clothing and wash before use.

After inhalation:

Supply fresh air and to be sure call for a doctor.

(Contd. on page 3)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 30.07.2018

Version number 1

Revision: 30.07.2018

Trade name: PU BETON 4006 COMPONENT B

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Clean with water and soap. If possible, also wash with polyethylene glycol 400.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Avoid strong water jet-risk of cornea damage, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray.

Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

Protective equipment:

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

6.1.1 For non-emergency personnel Avoid contact with dripping or leaking material

6.1.2 For emergency responders

First-aid responders must wear protective clothing, gloves, goggles and respiratory device.

6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation.

Do not breathe fume.

Avoid contact with eyes, hands and clothing.

Wash contaminated clothing before reuse.

Information about fire - and explosion protection: No special measures required.

(Contd. on page 4)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 30.07.2018

Version number 1

Revision: 30.07.2018

Trade name: PU BETON 4006 COMPONENT B

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities**Storage:** Store in cool, dry conditions in well sealed receptacles.**Requirements to be met by storerooms and receptacles:** Store in a cool location.**Information about storage in one common storage facility:** Not required.**Further information about storage conditions:** Keep container tightly sealed.**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**

WEL (Great Britain)	Short-term value: 0.07 mg/m ³
	Long-term value: 0.02 mg/m ³
	Sen; as -NCO

8.2 Exposure controls**8.2.1. Appropriate engineering controls**

Take appropriate protective measures with regard to the handling of chemicals and mixtures.

Personal protective equipment**General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing.

Avoid contact with the eyes and skin.

Do not eat, drink or smoke while using the product.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

For high concentrations of ABEK-P2 filter type.

Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Butyl rubber, BR - 0,7 mm

Nitrile rubber, NBR- 0,4 mm

Fluoro carbon rubber - FKM (0,4 mm)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 30.07.2018

Version number 1

Revision: 30.07.2018

Trade name: PU BETON 4006 COMPONENT B

(Contd. of page 4)

Penetration time of glove material

The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye protection:

Tightly sealed goggles

Body protection:

Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Appearance:**

Form:	Liquid
Colour:	Pale brown
Odour:	Characteristic
Odour threshold:	Not determined

pH value: Not applicable

Melting point/freezing point: -30 °C

Initial boiling point and boiling range: 300 °C

Flash point: >200 °C

Flammability (solid, gas): Product is not flammable.

Auto-ignition temperature: >600 °C

Decomposition temperature: Not determined

Auto-ignition temperature: Not determined.

Explosive properties: Product does not present an explosion hazard.

Explosion limits:

Lower:	Not determined
Upper:	Not determined

Vapour pressure at 20 °C: 11 hPa

Density at 20 °C: 1.23 g/cm³ (DIN EN ISO 2811-2)

Relative density Not determined

Vapour density Not applicable

Evaporation rate Not applicable

(Contd. on page 6)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 30.07.2018

Version number 1

Revision: 30.07.2018

Trade name: PU BETON 4006 COMPONENT B

(Contd. of page 5)

Solubility in / Miscibility with water:

Hydrolyses

Partition coefficient: n-octanol/water: Not determined

Viscosity:

Dynamic at 25 °C:

90-130 mPas (DIN EN ISO 3219)

Kinematic:

Not applicable

Solvent content:

Solids content:

100.0 %

9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity Stable under normal conditions

10.2 Chemical stability Material is stable under normal conditions.

Thermal decomposition / conditions to be avoided Stable at environment temperature.

10.3 Possibility of hazardous reactions

Reacts with alcohols.

Reacts with strong acids.

Reacts violently with water.

Exothermic polymerisation

10.4 Conditions to avoid No further relevant information available.

10.5 Incompatible materials No further relevant information available.

10.6 Hazardous decomposition products Corrosive gases/vapours

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Harmful if inhaled.

LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative	LC50/4 h (vapour)	1.5 mg/l
------------	-------------------	----------

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Inhalative	LC50/4 h (vapour)	0.31 mg/l (rat) (OECD 401)
------------	-------------------	----------------------------

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Sensitisation Sensitization possible through skin contact

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Carc. 2

Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 30.07.2018

Version number 1

Revision: 30.07.2018

Trade name: PU BETON 4006 COMPONENT B

(Contd. of page 6)

Carcinogenicity

Carcinogen, Category 2

Suspected of causing cancer.

Reproductive toxicity Based on available data, the classification criteria are not met.**STOT-single exposure**

The product is classified as Specific Target Organ Toxicity after single exposure Category 3

May cause respiratory irritation.

STOT-repeated exposure

STOT Repeated Exposure Category 2

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazardNot classified as a risk for aspiration according to paragraphs 3.10.3.3.1.1. & 3.10.3.3.1.2 of CLP Regulation 1272/2008 / EC. The viscosity of the mixture at 40 ° C is greater than 20.5 mm² / s.**SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity:****CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues**


EC50(24h) >1000 mg/l (daphnia magna)

LC50-96h >1000 mg/l (Brachydanio rerio)

NOEL, 21 days >10 mg/l (daphnia magna)

12.2 Persistence and degradability No further relevant information available.**12.3 Bioaccumulative potential** No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Other adverse effects** No further relevant information available.**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Recommendation**

Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

Waste disposal key:

08 04 09 - waste adhesives and sealants containing organic solvents or other dangerous substances.

(Contd. on page 8)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 30.07.2018

Version number 1

Revision: 30.07.2018

Trade name: PU BETON 4006 COMPONENT B

(Contd. of page 7)

Uncleaned packaging:**Recommendation:** Disposal must be made according to official regulations.**SECTION 14: Transport information****14.1 UN-Number**

ADR, ADN, IMDG, IATA Void

14.2 UN proper shipping name

ADR, ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR, ADN, IMDG, IATA

Class Void

14.4 Packing group

ADR, IMDG, IATA Void

14.5 Environmental hazards: Not applicable.**14.6 Special precautions for user** Not applicable.**14.7 Transport in bulk according to Annex II of**

Marpol and the IBC Code Not applicable.

UN "Model Regulation": Void

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

REACH Regulation 1907/2006/EC

Regulation (EU) 2015/830

CLP Regulation 1272/2008/EC

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Council Directive 94/33/EC on the protection of young people at work, as ammended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as ammended

Directive 2012/18/EU**Named dangerous substances - ANNEX I**

None of the ingredients is listed.

Substance is not listed.

National regulations:**Other regulations, limitations and prohibitive regulations****Substances of very high concern (SVHC) according to REACH, Article 57**

The substance is not SVHC.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2015/830 and Regulation No 1272/2008/EC (CLP)

Printing date 30.07.2018

Version number 1

Revision: 30.07.2018

Trade name: PU BETON 4006 COMPONENT B

(Contd. of page 8)

Training hints

Suitable training on safety in handling, storing and converting the product should be given to the employees based on all the existing information.

Department issuing SDS:

SUSTCHEM Engineering SA
 REACH & Chemical Services Department
 144, 3rd Septemvriou, GR 112 51, Athens, Greece
 Tel.: +30 210 8252510 Fax: +30 210 8252575
 E-mail: info@suschem.gr
 Website: www.sustchem.gr

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Resp. Sens. 1: Respiratory sensitisation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Carc. 2: Carcinogenicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

GB