

THIXOTROPIC AGENT IN WHITE FIBERS FORM

DESCRIPTION

STELLMITTEL 5 FT is a Thixotropic agent, in white fibers form. Easy and dust-free incorporation. Ideal for mortar mixtures. Suitable for PU 410.

RECOMMENDED FOR

- ▶ Thixotropic agent for primer EP 50 when used on walls as well as joint sealing.
- ▶ Thixotropic agent for coatings e.g. EP 200 VF for coatings with slope.
- ▶ Thixotropic agent for resin mortar e.g. EP 150 for concave and triangular covings.

ADVANTAGES

- ▶ Easy to apply. Ready to use.

TECHNICAL CHARACTERISTICS

Type	White Fibers
Density	80 g/l
Dosage	2-5 by weight of resin, depending on the application

The aforementioned results are related to average laboratory test results. In reality the climate changes, such as temperature, moisture and surface porosity may change these results.

DIRECTIONS FOR USE

Surface preparation: Mix the resin with the hardener according to the instructions in the technical data sheet. Afterwards, add the thixotropic agent STELLMITTEL 5 FT to the required dosage and continue the mixing. If necessary add more product. e.g. for resin mortar add 120-150 g (about 3 liters of volume).

NOTE: The surface preparation is very important for optimum result and high durability.

SPECIAL CONSIDERATIONS

Contact PENETRON HELLAS S.A. for further information, regarding your project.

PACKAGING

STELLMITTEL 5 FT is available 1.5 kg container.

STORAGE / SHELF LIFE

When stored in dry rooms, protected against UV and heat the shelf life is unlimited.

SAFE HANDLING INFORMATION

Avoid skin and eye contact. If contact is made, flush areas with lots of water and seek medical advice. Protective gloves, mask and goggles should be worn. For further information please refer to Safety Data Sheet. PENETRON HELLAS S.A. has recently updated Safety Data Sheet on the safe use of PENETRON® products. Each Safety Data Sheet contains health and safety information for the protection of your employees and your customers. **KEEP OUT OF REACH OF CHILDREN.**



THIXOTROPIC AGENT IN WHITE FIBERS FORM

WARRANTY – DISCLAIMER

PENETRON HELLAS S.A. warrants that its products are manufactured under certified ISO Standard procedures, are of excellent quality and shall be free from material defects and contain all components in their proper proportion. Should any of the products be proven defective, the liability to PENETRON HELLAS S.A. shall be limited to replacement of the material proven to be defective, since the standard application procedures have been met and the suitability of the product for the particular application have been proven. PENETRON HELLAS S.A. makes no warranty as to merchantability of fitness for a particular purpose. User, after contacting the distributor of the product, shall determine the suitability of the product for his intended use and assume all risks and liability in connection therewith. While every care has been taken, the information provided in this product's data sheet make no part of any contract. All recommendations, technical data and test data contained in this product's data sheet are based upon the results of control laboratory tests or in actual field tests. However, PENETRON HELLAS S.A. makes no warranty of any kind, concerning this data. In any case, this data are given in good faith based in the PENETRON HELLAS S.A. experience, till the publication of this sheet. Due to variance in storage, handling and applications of the materials, PENETRON HELLAS S.A. accepts no liability for the results obtained. It is suggested that potential users try small applications to determine the suitability of each individual product for their specific requirements. The users should always refer to the most recent edition of the product's data sheet. PENETRON HELLAS S.A. may particularly differentiate its versions of the product's data sheet compared with those of PENETRON INTERNATIONAL LTD or respective PENETRON companies worldwide. These changes are due to text formatting, different application weathering and procedures or different product names and aim at the optimal consumer information

PENETRON HELLAS S.A.
G.E.MH. No: 07278001000
Athens Headquarters - Greece
50 - 52, Thrakomakedonon Av.
136 79 Acharnes, Greece
T: +30 210 2448250
F: +30 210 2476803
info@penetron.gr, www.penetron.gr