

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A**1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

Application of the substance / the mixture:

Epoxy resin

Epoxy coating

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

PENETRON HELLAS S.A. G.E.MH. No: 07278001000

50, THRAKOMAKEDONON AV., 136 79 ACHARNES, GREECE

TEL.: +30 210 2448250 - FAX: + 30 210 2476803

Email: info@penetron.gr Site: www.penetron.gr

1.4 Emergency telephone number:

European Emergency Tel.: 112

*

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation EC No 1272/2008 CLP:**

GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

2.2 Label elements**Labelling according to Regulation EC No 1272/2008 CLP:**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms:

GHS07 GHS09

Signal word: Warning

(Contd. on page 2)

— EN —

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 1)

Hazard-determining components of labelling:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane
 oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH205 Contains epoxy constituents. May produce an allergic reaction.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

* **SECTION 3: Composition/information on ingredients**

3.2 Mixtures**Description:** Mixture: consisting of the following components.**Ingredients according Regulation (EU) 2020/878:**

CAS: 1675-54-3 EINECS: 216-823-5 Index number: 603-073-00-2	2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Specific concentration limits: Eye Irrit. 2; H319: C ≥ 5 % Skin Irrit. 2; H315: C ≥ 5 %	25-50%
CAS: 100-51-6 EINECS: 202-859-9 Index number: 603-057-00-5 Reg.nr.: 01-2119492630-38-XXXX	Benzyl alcohol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332	2.5-10%
CAS: 68609-97-2 EINECS: 271-846-8 Index number: 603-103-00-4 Reg.nr.: 01-2119485289-22-XXXX	oxirane, mono[(C12-14-alkyloxy)methyl] derivs. ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-<10%

(Contd. on page 3)

-EN-

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 2)

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Seek immediate medical advice.

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Remove contact lenses and continue rinsing for several minutes

Avoid strong water jet-risk of cornea damage, consult a doctor.

After swallowing:

Immediately rinse the mouth with water.

Never give anything by mouth to an unconscious person.

Consult a physician or poison control center.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Self contained breathing apparatus and full protective clothing must be worn in case of fire.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin and eyes.

Avoid inhalation of vapors.

Ensure adequate ventilation.

6.1.1 For non-emergency personnel

Avoid contact with dripping or leaking material

6.1.2 For emergency responders

First-aid responders must wear protective clothing, gloves, goggles and respiratory device with filter type A.

6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

(Contd. on page 4)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 3)

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material: (sand, diatomite, acid binders, universal binders and sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation.

Avoid inhaling vapors.

Avoid contact with skin and eyes.

Do not eat, drink or smoke when using this product.

Wash your hands thoroughly after handling.

Wash contaminated clothes before reusing them.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage: Store in tightly closed containers, in a cool and dry place with good ventilation.

Requirements to be met by storerooms and receptacles: Store in a cool and dry place.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

7.3 Specific end use(s) No further relevant information available.

* SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs

(CAS: 1675-54-3) 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Workers:

Inhalation - Long-term exposure, Systemic effects: 4.93 mg/m³

Dermal - Long-term exposure, systemic effects: 0.75 mg/kg bw/d

Consumers:

Inhalation - Long-term exposure, Systemic effects: 0.87 mg/m³

Dermal - Long-term exposure, systemic effects: 89.3 mg/kg bw/d

Oral - Long-term exposure, Systemic effects: 0.5 mg/kg bw/d

(CAS: 100-51-6) benzyl alcohol

Consumers:

Short-term exposure, acute systemic effects, oral: 20 mg/kg

Long-term exposure, systemic effects, oral: 4 mg/kg

Short-term exposure, systemic effects, inhalation: 27 mg/m³

Long-term exposure, systemic effects, inhalation: 5.4 mg/m³

Workers:

Short-term exposure, systemic effects, inhalation: 110 mg/m³

Long-term exposure, systemic effects, inhalation: 22 mg/m³

Short-term exposure, systemic effects, dermal: 40 mg/kg

Long-term exposure, systemic effects, dermal: 8 mg/kg

(Contd. on page 5)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 4)

(CAS: 68609-97-2) Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Workers:

Inhalation - Long-term exposure, Systemic effects: 3,6 mg/m³

Dermal - Long-term exposure, Systemic effects: 1 mg/kg bw/d

Consumers:

Inhalation - Long-term exposure, Systemic effects: 0.87 mg/m³

Dermal - Long-term exposure, Systemic effects: 0,5 mg/kg bw/d

Oral - Long-term exposure, Systemic effects: 0,5 mg/kg bw/d

PNECs

(CAS: 1675-54-3) 2,2'-[(1-methylethylidene) bis(4,1phenylenoxymethylene)] bis-oxiranium.

STP: 10 mg/l

Fresh water: 0.006 mg/l

Fresh water (intermittent releases): 0.018 mg/L

Sediment (freshwater): 0.341 mg/kg sediment dw

marine water: 0.001 mg/l

Sediment (marine water): 0.034 mg/kg sediment dw

Soil: 0.065 mg/kg soil dw

Secondary poisoning: 11 mg/kg food

(CAS: 68609-97-2) Oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Fresh water: 0,106 mg/L

Fresh water (intermittent releases): 0,072 mg/L

Marine water: 0,011 mg/L

STP: 10 mg/L

Sediment (fresh water): 307,16 mg/kg sediment dw

Sediment (marine water): 30,72 mg/kg sediment dw

Soil: 1,234 mg/kg soil dw

(CAS: 100-51-6) benzyl alcohol

Soil: 0.456 mg/kg

Sewage treatment plant: 39 mg/l

Sediment marine water: 0,527 mg/kg

Marine water: 0.1 mg/l

Sediment fresh water: 5,27 mg/kg

Fresh water: 1 mg/l

Intermittent releases: 2.3 mg/L

8.2 Exposure controls**8.2.1. Appropriate engineering controls** Provide adequate ventilation.**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Be sure to clean skin thoroughly after work and before breaks.

Avoid contact with skin and eyes.

Do not breathe vapours or mists.

Do not eat, drink or smoke while using the product.

Remove contaminated clothes and wash before reusing them.

(Contd. on page 6)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 5)

Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Hand protection

Protective gloves resistant to chemicals (standard EN 374-1)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR - 0,7 mm, Nitrile rubber, NBR- 0,4 mm

Penetration time of glove material

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions.

Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye/face protection

Tightly sealed goggles (EN 166).

Body protection:

Protective work clothing

Environmental exposure controls Prevent enter of the product into drains, surface and groundwater and soil.

*

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Physical state**

Liquid

Colour:

Different according to colouring

Odour:

Characteristic

Odour threshold:

Not determined

Boiling point or initial boiling point and boiling range

>200 °C

Flammability

Not applicable

Lower and upper explosion limit**Lower:**

Not determined

Upper:

Not determined

Flash point:

101 °C

Not Flammable

Auto-ignition temperature:

435 °C

Decomposition temperature:

Not determined

(Contd. on page 7)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 6)

pH	Not determined
Viscosity:	
Kinematic viscosity	Not determined
Dynamic at 20 °C:	4,500 mPas
Solubility	
water:	Not miscible
Partition coefficient n-octanol/water (log value)	Not determined
Vapour pressure:	Not determined
Density and/or relative density	
Density at 20 °C:	1.68 g/cm ³
Relative density	Not determined
Vapour density	Not determined

9.2 Other information**Appearance:****Form:** Liquid**Important information on protection of health and environment, and on safety.****Ignition temperature:** Product is not selfigniting.**Explosive properties:** Product does not present an explosion hazard.**Cloud point / clarification point:****Oxidising properties** Not oxidising**Evaporation rate** Not determined**Information with regard to physical hazard classes**

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity**10.1 Reactivity** Stable under normal conditions**10.2 Chemical stability** Material is stable under normal conditions.**Thermal decomposition / conditions to be avoided** Stable at environment temperature.

(Contd. on page 8)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 7)

10.3 Possibility of hazardous reactions

Exothermic polymerisation.

Reacts with alcohols, amines, aqueous acids and alkalis.

10.4 Conditions to avoid No further relevant information available.**10.5 Incompatible materials** No further relevant information available.**10.6 Hazardous decomposition products** Irritant gases/vapours

*

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****ATE (Acute Toxicity Estimates)**

Oral	LD50	12,300-49,200 mg/kg (rat)
Inhalative	ATEmix (vapours)	110-440 mg/l (rat)

CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Oral	LD50	>2,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)

CAS: 100-51-6 Benzyl alcohol

Oral	LD50	1,230 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	ATEmix (vapours)	11 mg/l (rat)
	LC50	>4,178 mg/m ³ (rat)

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Oral	LD50	17,100 mg/kg (rat)
Dermal	LD50	>4,000 mg/kg (rabbit)

Skin corrosion/irritation Causes skin irritation.**Serious eye damage/irritation** Causes serious eye irritation.**Respiratory or skin sensitisation** May cause an allergic skin reaction.**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**Additional toxicological information:****Repeated dose toxicity** Based on available data, the classification criteria are not met.**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

EN

(Contd. on page 9)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 8)

*

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

CAS: 1675-54-3 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

EC50 (72h)	>11 mg/l (algae)
EC50 (48h)	1.8 mg/l (Daphnia magna)
LC50 (96h)	2 mg/l (Oncorhynchus mykiss)
NOEC (21d)	0.3 mg/l (Daphnia magna)
NOEC(72h)	4.2 mg/l (Daphnia magna)

CAS: 100-51-6 Benzyl alcohol

EC50 (72h)	770 mg/l (algae)
------------	------------------

CAS: 68609-97-2 oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

EC50 (72h)	844 mg/l (algae) (Freshwater Alga and Cyanobacteria, Grow Inhibition)
EC50 (48h)	7.2 mg/l (Daphnia magna) (Daphnia sp. Acute Immobilisation Test)
LC50 (96h)	1.8 mg/l (Rainbow Trout) (Fish, Acute Toxicity Test)
	>5 mg/l (Lepomis macrochirus (Bluegill)) (Fish, Acute Toxicity Test)
EC50(3h)	>100 mg/l (Activated Sludge) (Activated Sludge, Respiration Inhibition Test)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Remark: Toxic for fish

Additional ecological information:

General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Also poisonous for fish and plankton in water bodies.

The product contains materials that are harmful to the environment.

EN

(Contd. on page 10)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 9)

*


SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation



Dispose according to National Regulations.



Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Contact manufacturer for recycling information.

European waste catalogue

HP4	Irritant - skin irritation and eye damage
HP13	Sensitising
HP14	Ecotoxic

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

*

SECTION 14: Transport information

14.1 UN number or ID number

ADR, IMDG, IATA

UN3082

14.2 UN proper shipping name

ADR

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane)

IMDG


ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane), MARINE POLLUTANT

IATA

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane)

14.3 Transport hazard class(es)

ADR, IMDG, IATA



Class

9 Miscellaneous dangerous substances and articles.

Label

9

14.4 Packing group

ADR, IMDG, IATA

II

(Contd. on page 11)

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 10)

14.5 Environmental hazards:	Environmental Hazardous
Marine pollutant:	Yes
	Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
Special marking (IATA):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
Hazard identification number (Kemler code):	90
EMS Number:	F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	(-)

IMDG

Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (2,2'-[(1-METHYLETHYLIDENE)BIS(4,1-PHENYLENEOXYMETHYLENE)]BISOXIRANE), 9, II

*

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH Regulation 1907/2006/EC

Regulation (EU) 2020/878

CLP Regulation 1272/2008/EC

Directive 98/24/EC on the protection of health and safety of workers from the risks related to chemicals agents at work.

Council Directive 94/33/EC on the protection of young people at work, as ammended.

Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding, as ammended

Directive 2012/18/EU

Named dangerous substances - ANNEX I The substance is not included in Annex I.

Seveso category E2 Hazardous to the Aquatic Environment

Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

(Contd. on page 12)

EN

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 11)

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57

It doesn't contain substances of very high concern (SVHC).

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

*

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H411 Toxic to aquatic life with long lasting effects.

Training hints

Suitable training on safety in handling, storing and converting the product should be given to the employees based on all the existing information.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritation

Serious eye damage/irritation

Skin sensitisation

Hazardous to the aquatic environment - long-term
(chronic) aquatic hazard

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 13)

EN

Safety data sheet
complying with Regulation 1907/2006/EC (REACH Regulation),
EU 2020/878 and Regulation No 1272/2008/EC (CLP)

Printing date 04.07.2023

Version number 2 (replaces version 1)

Revision: 04.07.2023

Trade name: PARKHAUS-Oberflächenschutzsystem KLB-SYSTEM EPOXID EP 5530 Component A

(Contd. of page 12)

Department issuing SDS:

SUSTCHEM S.A.
 REACH & Chemical Services Department
 A: 144, 3rd Septemvriou, GR 112 51 | Athens, Greece
 T: +30 210 8252510 | F: +30 210 8252575
 W: www.sustchem.gr | E: info@suschem.gr

Version number of previous version: 1**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (REACH)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 Skin Sens. 1: Skin sensitisation – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**